

Technical Data Specification Sheet

Kraft Paper Packed 1/3U Montmorillonite Desiccant

- Product Kraft Paper Packed 1/3U Montmorillonite Desiccant
- Product Code 2MTKP302A

Raw Material 0.5~2mm Montmorillonite

Packaging Kraft Paper

Material

Technical Standard

Items		Standard
Appearance		The surface of desiccant bag should not have damage or obvious discoloration, with the flat paper. The printing is clear without stains.
Loss on Drying		≤2.0%
Unit Moisture adsorption capacity	RH=20%	≥2.85g
25°C	RH=40%	≥5.70g
Unit Moisture adsorption speed	RH=40%	≥0.25g/7h
23°C, RH=40%	RH=80%	≥0.7g/7h
Particle Size (12.5~0.177mm)		≥96.0%
Dust Permeability Per Unit		< 0.5mg
Unit Mass		≤50g
Unit Volume		≤45.0ml
Dropping resistance		In the case of free falling of 20 times at a height of 3m, the desiccant bag shall not be broken or have the damage of enabling the adsorbent to leak.

Pouch	Gross Weight:	12.0~12.6g
Dimension	Width:	57±3mm
	Length:	80±4mm

Sealing Method Back Seal

Printing Wisesorbent





Technical Data Specification Sheet

Kraft Paper Packed 1/3U Montmorillonite Desiccant

STD Packaging— 900pcs/PE bag/drum
Drum Dimension: \$\$\phi\$ 275×345 mm
—Drum label contains the following:
PO Number
Product Name
Specification
Quantity
Batch Number
MADE IN USA

 Storage
 Shelf life: 2 years

 Desiccant must always be kept in airtight containers to avoid moisture.

Notes The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.

2022-10-01

