

Technical Data Specification Sheet

Kraft Paper Packed 1/6U Montmorillonite Desiccant

Product Kraft Paper Packed 1/6U Montmorillonite Desiccant

Product Code 2MTKP301A

Raw Material 0.5~2mm Montmorillonite

Packaging

Kraft Paper

Material

Technical Standard

Items	Standard	
Appearance	The surface of desiccant bag should not have damage or obvious discoloration, with the flat paper. The printing is clear without stains.	
Loss on Drying	≤2.0%	
Unit Moisture adsorption capacity	RH=20%	≥2.85g
25°C	RH=40%	≥5.70g
Unit Moisture adsorption speed	RH=40%	≥0.25g/7h
23°C, RH=40%	RH=80%	≥0.7g/7h
Particle Size (12.5~0.177)	≥96.0%	
Dust Permeability Per U	< 0.5mg	
Unit Mass	≤50g	
Unit Volume	≤45.0ml	
Dropping resistance	In the case of free falling of 20 times at a height of 3m, the desiccant bag shall not be broken or have the damage of enabling the adsorbent to leak.	

Pouch

Gross Weight:

6.1~6.4g

Dimension Width:

57±3mm

Length:

65±3mm

Sealing Method

Back Seal

Printing

Wisesorbent





Technical Data Specification Sheet

Kraft Paper Packed 1/6U Montmorillonite Desiccant

STD Packaging — 1500pcs/PE bag/drum

Drum Dimension: φ 275×345 mm
—Drum label contains the following:

PO Number Product Name Specification Quantity

Batch Number MADE IN USA

Storage Shelf life: 2 years

Desiccant must always be kept in airtight containers to avoid moisture.

Notes The data given here is based on current knowledge and experience. This document is

designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable

for his own operation.

2022-10-01

