

Technical Data Specification Sheet

Tyvek Packed 10g High Performance Desiccant

Product Tyvek Packed 10g High Performance Desiccant

Product Code A4MCTF0003

Raw Material Magnesium salt and Polymer

Packaging Material Tyvek coated film

Technical Standard

Items		Standard
Appearance		The surface of desiccant bag should not have damage or obvious discoloration, with the flat paper. The printing is clear without stains.
Moisture adsorption capacity 25°C	RH=20%	≥40%
	RH=50%	≥70%
	RH=90%	≥180%
Moisture adsorption speed 23°C, RH=90%, 24h		≥40%
Infiltration test (25°C、RH=80%)		No liquid penetration from surface

Sachet Gross Weight: 11.0~12.0g

Dimension Width: 80±4mm

Length: 100±5mm

Sealing Method 4 Sides Seal

Printing Wisesorbent

STD Packaging — 1000pcs/4foil bags/carton
 Carton Size: 370×275×250 mm, 48ctns/pallet
 —Carton label contains the following:

- PO Number
- Product Name
- Specification
- Quantity
- Batch Number
- MADE IN USA



Technical Data Specification Sheet

Tyvek Packed 10g High Performance Desiccant

Storage Shelf life: 1 year
Desiccant must always be kept in airtight containers to avoid moisture.

Notes The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.

2020-03-05

