

Technical Data Specification Sheet

62.5g*24 Strips Container Desiccant

Product 62.5g*24 Strips Container Desiccant

Product Code 4HATF0005A

Raw Material Calcium Chloride and High-molecular Polymer

Packaging Material Flash PE + Nonwoven Coated Film + PA Film

Technical Standard

Items			Standard
Appearance			The surface of desiccant bag should not have damage or obvious discoloration, with the flat paper. The printing is clear without stains.
Moisture adsorption capacity 38°C, RH=90%			≥350%
Moisture adsorption speed 38°C, RH=90%, 24h			≥20%
Simulation of daily climatic changes during container transport	20°C, RH=90%	8h	After circulating test for 45 days, moisture adsorption capacity ≥180%
	Changing to 40°C, RH=60%	6h	
	40°C, RH=60%	2h	
	Changing to 20°C, RH=90%	8h	

Dimension

Gross Weight: 1520~1820g

Width: 500±20mm

Length: 1200±50mm

Sealing Method 4 Sides Seal

Printing Wisepower

STD Packaging — 7strips/double PE bags/carton

Carton Size: 540×275×325 mm, 24ctns/pallet

—Carton label contains the following:

PO Number

Product Name

Specification

Quantity

Batch Number



Technical Data Specification Sheet

62.5g*24 Strips Container Desiccant

Storage

Shelf life: 1 year

Desiccant must always be kept in airtight containers to avoid moisture.

Notes

The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.

2023-02-14

