

Technical Data Specification Sheet

Flash PE Coated Film+ PET Film Packed 10g Indicating High Absorption Desiccant

Product Flash PE Coated Film+ PET Film Packed 10g Indicating High Absorption Desiccant

Product Code 4HATF103A

Raw Material Calcium Chloride, Modified Starch and Diatomite

Packaging

Flash PE Coated Film + PET Film

Material

Technical Standard

Items	Standard
Appearance	The surface of desiccant bag should not have damage or obvious discoloration, with the flat paper. The printing is clear without stains.
Moisture adsorption capacity 25°C, RH=90%	≥200%
Infiltration test (25°C、RH=90%)	No liquid penetration from surface

Sachet Gross Weight: 11.3~13.0g **Dimension** Width: 100±5mm

Length: 110±6mm

Sealing Method Four Sides Seal

Printing Wisepower

STD Packaging — 650pcs/PE bag/drum

Drum Size: ϕ 275*345mm, 63drums/pallet

—Carton label contains the following:

PO Number Product Name Specification Quantity Batch Number





Technical Data Specification Sheet

Flash PE Coated Film+ PET Film Packed 10g Indicating High Absorption Desiccant

Storage Shelf life: 2 years

Desiccant must always be kept in airtight containers to avoid moisture.

Notes The data given here is based on current knowledge and experience. This document is

designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable

for his own operation.

2023-02-14

