

## Technical Data Specification Sheet

### Flash PE Coated Film+ PET Film Packed 30g Indicating High Absorption Desiccant

**Product** Flash PE Coated Film+ PET Film Packed 30g Indicating High Absorption Desiccant

**Product Code** 4HATF104A

**Raw Material** Calcium Chloride, Modified Starch and Diatomite

**Packaging Material** Flash PE Coated Film + PET Film

**Technical Standard**

Items	Standard
Appearance	The surface of desiccant bag should not have damage or obvious discoloration, with the flat paper. The printing is clear without stains.
Moisture adsorption capacity 25°C, RH=90%	≥200%
Infiltration test (25°C、RH=90%)	No liquid penetration from surface

**Sachet Dimension**  
 Gross Weight: 31~36g  
 Width: 100±5mm  
 Length: 160±8mm

**Sealing Method** Four Sides Seal

**Printing** Wisepower

**STD Packaging**  
 — 250pcs/PE bag/drum  
 Drum Size: φ 275\*345mm, 63drums/pallet  
 —Carton label contains the following:  
 PO Number  
 Product Name  
 Specification  
 Quantity  
 Batch Number



## Technical Data Specification Sheet

### Flash PE Coated Film+ PET Film Packed 30g Indicating High Absorption Desiccant

**Storage**

Shelf life: 2 years

Desiccant must always be kept in airtight containers to avoid moisture.

**Notes**

The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.

2023-02-14

