

Technical Data Specification Sheet

Flash PE Coated Film+ PET Film Packed 50g High Absorption Desiccant

Product Flash PE Coated Film+ PET Film Packed 50g High Absorption Desiccant

Product Code 4HATF105A

Raw Material Calcium Chloride, Modified Starch and Diatomite

Packaging Material Flash PE Coated Film + PET Film

Technical Standard

Items	Standard
Appearance	The surface of desiccant bag should not have damage or obvious discoloration, with the flat paper. The printing is clear without stains.
Moisture adsorption capacity 25°C, RH=90%	≥200%
Infiltration test (25°C、RH=90%)	No liquid penetration from surface

Sachet Dimension
 Gross Weight: 51~59g
 Width: 120±6mm
 Length: 170±9mm

Sealing Method Four Sides Seal

Printing Wisepower

STD Packaging
 —160pcs/PE bag/drum
 Drum Size: φ 275*345mm, 63drums/pallet
 —Carton label contains the following:
 PO Number
 Product Name
 Specification
 Quantity
 Batch Number



Technical Data Specification Sheet

Flash PE Coated Film+ PET Film Packed 50g High Absorption Desiccant

Storage Shelf life: 2 years
Desiccant must always be kept in airtight containers to avoid moisture.

Notes The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.

2023-02-14

