

## **Technical Data Specification Sheet**

## Flash PE Coated Film+ PET Film Packed 100g Indicating High Absorption Desiccant

Product Flash PE Coated Film+ PET Film Packed 100g Indicating High Absorption Desiccant

S

Product Code 4HATF106A

Raw Material Calcium Chloride, Modified Starch and Diatomite

Packaging Flash PE Coated Film + PET Film

Material

Technical Standard

| Items                                     | Standard   |
|---|--|
| Appearance                                | The surface of desiccant bag should not have<br>damage or obvious discoloration, with the flat<br>paper. The printing is clear without stains. |
| Moisture adsorption capacity 25°C, RH=90% | ≥200%  |
| Infiltration test (25°C, RH=90%)          | No liquid penetration from surface   |

| Sachet    | Gross Weight: | 100~116g |
|-----------|---------------|----------|
| Dimension | Width:        | 150±8mm  |
|           | Length:       | 200±10mm |

Sealing Method Four Sides Seal

Printing Wisepower


 STD Packaging
 —80pcs/PE bag/drum

 Drum Size:
 Φ 275\*345mm, 63drums/pallet

 —Carton label contains the following:
 PO Number

 Product Name
 Specification

 Quantity
 Batch Number







## **Technical Data Specification Sheet**

## Flash PE Coated Film+ PET Film Packed 100g Indicating High Absorption Desiccant

 Storage
 Shelf life: 2 years

 Desiccant must always be kept in airtight containers to avoid moisture.

Notes The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.

2023-02-14

