

Technical Data Specification Sheet

Tyvek packed 0.25g Silica Gel Desiccant

Product Tyvek packed 0.25g Silica Gel Desiccant

Product Code 1SGTY000A

Raw Material Type A 0.5~1.5mm irregular Silica Gel

Packaging Material Uncoated Tyvek

Technical Standard

Items	Standard
Appearance	The surface of desiccant bag should not have damage or obvious discoloration, with the flat paper. The printing is clear without stains. The transparency of the back seal for each pack of product should be more than 50%.
Loss on Drying	≤3.0%
Moisture adsorption capacity 25°C	RH=40% ≥19.0%
	RH=80% ≥27.0%
Dropping resistance	In the case of free falling of 15 times at a height of 1.2m or more, the desiccant bag shall not be broken or have the damage of enabling the adsorbent to leak.
Decoloring test	The soaked solution should be colorless.
Total residual solvents	≤5mg/m ²
Benzene residues	Not detectable
* Lead	≤5ppm
Paper bag fluorescence	No flaky fluorescence
Total bacterial count (cfu / bag)	≤10 ³
Mould and yeast count (cfu / bag)	≤10 ²
Escherichia coli	Not detectable per bag

Sachet Net Weight: 0.24~0.26g

Dimension Width: 16±1mm
Length: 23±1mm

Sealing Method Melting Seal

Printing Wisemini



Technical Data Specification Sheet

Tyvek packed 0.25g Silica Gel Desiccant

STD Packaging — 12000pcs/PE/drum
Drum Size: ϕ 275*345mm, 48drums/pallet
—Carton label contains the following:
PO Number
Product Name
Specification
Quantity
Batch Number
MADE IN USA

Storage Shelf life: 2 years
Desiccant must always be kept in airtight containers to avoid moisture.

Notes The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.

2023-02-14

