

Technical Data Specification Sheet

3g Canister Desiccant

Product 3g Canister Desiccant

Product Code 6SGPL503A

Raw Material Type A、1~3mm beaded Silica Gel

Packaging Material Plastic Shell

Technical Standard

Items		Standard
Appearance		Shell should be in perfect condition without broken; Laser should be clear and no stains.
Loss on Drying		≤3.0%
Moisture adsorption capacity 25°C	RH=40%	≥19.0%
	RH=80%	≥27.0%
Dropping resistance		In the case of free falling of 15 times at a height of 1m or more, the plastic shell shall not be broken and the adsorbent shall not leak.
Decoloring test		The soaked solution should be colorless.
Total residual solvents		≤5mg/m ²
* Lead		≤5ppm
Fiber sheet fluorescence		No flaky fluorescence
Total bacterial count (cfu / bag)		≤10 ³
Mould and yeast count (cfu / bag)		≤10 ²
Escherichia coli		Not detectable per bag

Sachet Dimension

Net Weight: 2.8~3.3g

Gross Weight: 4.6~5.1g

Diameter: 19.5±0.5mm

Height: 25.5±0.5mm

Printing WISECAN
DO NOT EAT



Technical Data Specification Sheet

3g Canister Desiccant

STD Packaging — 1200pcs/PE/drum
Drum Size: ϕ 275*345mm, 63drums/pallet
—Carton label contains the following:
PO Number
Product Name
Specification
Quantity
Batch Number
MADE IN USA

Storage Shelf life: 2years
Desiccant must always be kept in airtight containers to avoid moisture.

Notes The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.

2023-02-14

