

Technical Data Specification Sheet

60*60mm Fiber Desiccant

- **Product** 60*60mm Fiber Desiccant
- Product Code 5CCPL004A
- Raw MaterialCalcium ChlorideFiber Sheet

Packaging PET Film

Material Comply with FDA 21cfr 177.1520 regulation of contacting with food directly

	Items		Standard
	Appearance		The surface of desiccant bag should not have damage or obvious discoloration, with the flat paper. The printing is clear without stains.
	Weight		600±30g/m ²
Technical Standard	Loss on Drying (120°C)		≤8.0%
	Moisture adsorption capacity 25°C	RH=20%	≥9.0%
		RH=50%	≥20.0%
		RH=90%	≥50.0%
	Infiltration Test $25\pm2^{\circ}$ C, RH =90±2%		No liquid
	*Heavy Metal (Pb)		≤ 1 mg/kg
	Total bacterial count (cfu		$\leq 10^{3}$
	Mould and yeast count (cfu / bag)		$\leq 10^2$
	Escherichia coli		Not detectable per bag
Sachet Thickness: 1.0±0.1mm			
Dimension	Width: 60±2mm		
	Length: 60±2mm		
Printing WiseFresh			
	 — 1000pcs/PE bag, 4000pcs/4PE bags/carton Carton Size: 370×275×250 mm, 48ctns/pallet —Carton label contains the following: PO Number Product Name Specification Quantity Batch Number 		





Technical Data Specification Sheet

60*60mm Fiber Desiccant

Storage Shelf life: 1year

Desiccant must always be kept in airtight containers to avoid moisture.

NotesThe product couldn't contact with aqueous and fatty foods directly.The data given here is based on current knowledge and experience. This document is
designed to describe the products in terms of their safety requirements. The above details do
not imply any guarantee concerning composition, properties or performance. User is liable
for his own operation.

2023-02-14

