

Technical Data Specification Sheet

Flash PE packed 10g Silica Gel Desiccant

Product Flahs PE packed 10g Silica Gel Desiccant

Product Code 2SGTG007A

Raw Material Type A, 0.5~2.0mm irregular Silica Gel

Packaging Material Coated Flash PE

Technical Standard

Items		Standard
Appearance		The surface of desiccant bag should not have damage or obvious discoloration, with the flat paper. The printing is clear without stains.
Loss on Drying		≤3.0%
Moisture adsorption capacity 25°C	RH=40%	≥19.0%
	RH=80%	≥27.0%
Dropping resistance		In the case of free falling of 15 times at a height of 1.2m or more, the desiccant bag shall not be broken or have the damage of enabling the adsorbent to leak.
Decoloring test		The soaked solution should be colorless.
Total residual solvents		≤5mg/m ²
Benzene residues		Not detectable
* Lead		≤5ppm
Paper bag fluorescence		No flaky fluorescence
Total bacterial count (cfu / bag)		≤10 ³
Mould and yeast count (cfu / bag)		≤10 ²
Escherichia coli		Not detectable per bag

Sachet Net Weight: 9.5~11.0g

Dimension Width: 38±2mm

Length: 90±4mm

Sealing Method Back Seal

Printing Wisemini



Technical Data Specification Sheet

Flash PE packed 10g Silica Gel Desiccant

STD Packaging — 750pcs/PE bag/pail
Pail Size: $\phi 275 \times 345$ mm, 48 drums/pallet
— Product label contains below:
Manufacturer
Product
Description
Quantity per carton
Batch No.
MADE IN USA

Storage Shelf life: 2 years
Desiccant must always be kept in airtight containers to avoid moisture.

Notes The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.

2023-02-14

